

TECHNOLOGY



Fast print/copy output of 42 ppm

Optional stapler inner-finisher

Downloadable apps to help you work faster and smarter

Advanced scan capture functionality right from the touchscreen control panel

Built-in Emperon® print system, PCL and PostScript emulation

Standard dual scan document feeder

Large 7" touchscreen with logical, intuitive menus — easy to operate, similar to a tablet Open API for seamless software integration

Compatibility with IC card readers for enhanced security

Standard wireless connectivity

Mobile printing support (AirPrint, Google Classic Cloud Print™, NFC)

Standard web browser

bizhub 4052

MONOCHROME COMPACT MULTIFUNCTION PRINTER

The bizhub 4052 is a valuable high volume solution for today's networked workflow delivering up to 42 ppm B&W output up to 1,200 dpi. The advanced Emperon print system and dual scan document feeder boost print/scan productivity, and standard wireless and intuitive touchscreen operation enhances versatility. All that is packaged with a low cost of operation to help reduce your expenses.

System memory	4 GB (when UK-219 is installed)		
System hard disk	250 GB (standard)		
Interface	10-Base-T / 100-Base-TX / 1,000-Base-T Ethernet, USB 2.0		
Network protocols	TCP/IP (IPv4 / IPv6), SMB 3.0, LPD, IPP, SNMP, HTTP, HTTPS		
Frame types	Ethernet 8021x		
Dual scan automatic	Up to 100 originals / 5.5" x 8.5" to 8.5" x 14" / 50-120 gsm		
document feeder			
Printable paper size	4" x 6" to 8.5" x 14" / custom paper sizes		
Printable paper weight	60-216 gsm		
Paper input capacity	Standard: 650 sheets Max.: 2,300 sheets		
Tray 1	550 sheets / 4" x 6" to 8.5" x 14" / 60 – 120 gsm		
Trays 2, 3 and 4 (optional)	550 sheets / 8.5" x 11 to 8.5 x 14" / 60-120 gsm		
Manual bypass	100 sheets / 4" x 6" to 8.5" x 14" / custom paper sizes /		
NSC-000000000005050500000	60-216 gsm		
Automatic duplexing	Letter, legal / 60-90 gsm		
Finishing modes	Staple (inline) up to 20 sheets (optional)		
Output capacity	Max.: 250 sheets		
Copy/print volume	Max.: 100,000 pages / month ²		
Toner lifetime	25,0001		
Imaging unit lifetime	60,000		
Power consumption	120 V / 60 Hz, less than 600 W (system)		
System dimensions	19.3" x 20.5" x 21.5" (W x D x H)		
System weight	Approx. 52 lb		
COPIER SPECIFICATIONS			
Copying process	Electrostatic laser copy, tandem, indirect		
Toner system	Simitri® HD Polymerized Toner		
Print speed	Up to 42 ppm (letter)		
Autoduplex speed	Up to 42 ppm (letter)		
1st copy out time	8.5 sec. or less		
Warm-up time	Approx. 37 sec.3		
Copy resolution	600 x 600 dpi		

Print speed	Up to 42 ppm (letter)
Autoduplex speed	Up to 42 ppm (letter)
1st copy out time	8.5 sec. or less
Warm-up time	Approx. 37 sec. ³
Copy resolution	600 x 600 dpi
Multi-copy	1-999
Original format	Max.: up to 8.5" x 14"
Magnification	25-400% in 1% steps, auto zooming
Copy functions	Electronic sorting, multi-job, adjustments (contrast, sharpness, image density), proof copy, interrupt mode, color mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1
SCANNER SPECIFICATIONS	
Casasasas	FO and the form of the first of the self-self-self-self-self-self-self-self-

SCANNER SPECIFICATION	NS .
Scan speed	50 opm (mono/single sided)
	100 opm (mono/duplex)
	32 opm (color/single sided)
	64 opm (color/duplex)
Scan resolution	600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-USB,
	Scan-to-HDD, Scan-to-DPWS, Network TWAIN
File formats	JPEG, TIFF, XPS, PDF, PDF/A(1b), Compact PDF
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Up to 400 job programs

PR	IN	TER	SP	EC	IF	CATI	ONS
Dri	nt	roce	dir	tio	•		

Print resolution	600 x 600 dpi, 1,200 x 1,200 dpi (reduced speed)
PDL	PCL5e/c emulation, PCL XL ver. 3.0, PostScript 3 emulation
	(3016), XPS ver. 1.0, OpenXPS, PDF 1.7
Operating systems	Windows (x64): 7 / 8.1 / 10
	Windows Server (x64): 2008 / 2008 R2 / 2012 / 2012 R2 / 2016
	Macintosh OS X 10.8 or later
	Linux / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3 Latin
Print functions	Direct print of TIFF, XPS, PDF and OOXML (DOCX, XLSX, PPTX),
	secure print, combination, n-up, poster, booklet
	page order, watermark

FAX SPECIFICATIONS

Fax	Super G3 (optional)	
Transmission	Analog, PC-fax	
Resolution	Max.: 600 x 600 dpi (ultra-fine)	
Compression	MH, MR, MMR, JBIG	
Modem	Up to 33.6 Kbps	
Destinations	2,100 (single + group)	
Functions	Time shift, PC-fax, fax forwarding, up to 400 program dials	

OPTIONS		
AU-205H	IC card reader / various IC card technologies	
DK-P02 Copier desk	Provides storage space for print media, adjustable height	
EK-605	Local USB interface kit	
EK-606	Local USB interface kit plus Bluetooth	
FK-517 Fax kit	Super G3 fax kit	
FS-P02 Inner finisher	Provides 20-sheet stapling	
KP-101 10 Key pad	For use instead of touchscreen	
LK-102 v3	Enhanced PDF encryption, PDF/A(1a/1b)	
	and linearized PDF support	
LK-104 v3	Voice guidance license kit	
LK-106	Supports native barcode printing	
LK-107	Supports native unicode printing	
LK-108	Supports native OCR A and B font printing	
LK-111	ThinPrint®, print data compression for reduced network impact	
PF-P15 Paper tray	Adds 250 sheet capacity / 8.5" x 11" to 8.5" x 14"	
	Add up to 3 units total (PF-P15 + PF-P16)	
PF-P16 Paper tray	Adds 550 sheet capacity / 8.5" x 11" to 8.5" x 14"	
	Add up to 3 units total (PF-P15 + PF-P16)	
UK-219 Expanded memory	2 GB memory extension ⁴	

SYSTEM FEATURES

AND DESCRIPTION OF THE PERSON NAMED IN COLUMN	- DOCTOR CONTROL OF THE STREET
Security	ISO 15408 EAL3 (in evaluation), IP filtering and port
	blocking, SSL2, SSL3 and TSL1.0 network communication,
	IPsec support, IEEE 802.1x support, user authentication,
	secure print, HDD overwrite (8 standard types), HDD data
	encryption, copy protection (print only)
Software	Net Care Device Manager, Web Connection, Konica Minolta Mobile,
	Print Status Notifier, Driver Packaging Utility

¹The bizhub 4052 ships with a starter toner cartridge (6,000 yield).





For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

© 2018 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo and bizhub are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com







Item #: 4052SS

²Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs.

Warm-up time may vary depending on the operating environment and usage.

⁴ Required for full functionality.